

UPAFLEX®

Channel baling presses with optional plastic wire or steel wire tying

CHANNEL BALING PRESSES OF THE SERIES







PRODUCT AND FURTHER PROCESSING

- Ideally suitable for the production of bales from RDF/SRF material or untreated domestic waste
- · No restrictions related to the binding material (plastic wire / steel wire) during the production of high dense bales
- · Further processing of the bales by different wrapping systems possible without any risks Bale lengths up to 2 mtr. possible by using
- single tying device Further processing of bales e.g. in incineration
 plants possible without any restrictions
- 2. AUTOMATIC TYING
 - Fully automatic tying optional with plastic wire or steel wire (vertically / horizontally) · Tying devices can be activated both as single
 - action device or together in double action · Plastic wire with cross-section 4 x 4 mm safe to
 - operate. No restrictions in tensile strength of the tying knot
 - Steel wire tying suitable for wire thicknesses up to 4,1 mm



- · Re-feeding of plastic wire coils easily to operate by integrated lifting system in combination with unreeling device
- · All elements of the tying device in contact with the pressing material made of stainless steel
- Adjustments for the treatment of different materials directly related to the chosen tying sequence (plastic wire or steel wire)















3. PRESS CHANNEL

- Fully machined pressbox with beaded floor including bolted wear plates. Jamming-free operation for press plate including all guiding elements due to beaded floor
- · Fully wear protection of all contact surfaces inside the press-box and the friction tunnel due to bolted wear plates

4. ELECTRICAL EQUIPMENT

1.

- Cabling at the baler completely protected with flexible steelflex protective tubing
- All electrical junction boxes including cable fittings made of stainless steel
- Electrical installation completely constructed according to protection category IP 65
- · Modular baler safety system via key transfer system including the prevention of lock-in danger



CHANNEL BALING PRESSES OF THE SERIES UPAFLEX®

UPAFLEX[®] ADVANTAGES

- Double-acting, two-fold tying system
- Fully automatic steel wire and plastic wire tying
- Tying mechanisms can be switched on or off completely independently from each other
- Highest flexibility in type-depending and mono operation
- Easiest handling high benefit
- Based on the successful UPAMAT series with all advantages
- Further processing of bales, e.g. in incineration plants possible without restrictions



UPAFLEX® IN ACTION

- In combined plants for compacting fuel and sorted recyclable materials
- For compacting untreated, unsorted domestic waste
- For processing of shredded domestic waste
- For compacting shredded industrial waste
- In production plants for sorted plastic fractions
- With 4-fold steel wire tying and additional 5-fold plastic wire tying in various and flexible fields of application





unoTech GmbH • Feldkoppel 17 • 49779 Niederlangen • Germany Phone: +49 5939 / 94 144 - 11 • Fax: +49 5939 / 94 144 - 30 info@unotech.de • www.unotech.de



UNOTECH®. INNOVATION DRIVEN BY EXPERIENCE.